



RBW6320G12851-8G MGB INPUT FLANGE INSTALLATION PULLER

9

SECTION A-A

- NOTES:
- 1) MATERIAL: 6061-T6 / 7075-T6
 - 2) HEAT TREAT: N/A
 - 3) FINISH: ANODIZE RED PER MIL-A-8625 TYPE 2 CLASS 2
 - 4) TOLERANCES: X.X = +/- 0.1" / +/- 1°
X.XX = +/- 0.01" / +/- 0.5°
X.XXX = +/- 0.005" / +/- 0.1°
X.XXXX = +/- 0.0005" / +/- 0.05°
PARALLELISM, ECCENTRICITY AND SYMMETRY ABOUT ALL CENTER LINES = +/- 0.005"
 - 5) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 6) BREAK SHARP EDGES: 0.005" TO 0.010"
 - 7) IDENTIFICATION: MACHINE ENGRAVE OR DOT MARK T/N AS SHOWN
 - 8) CENTER DRILL IS ACCEPTABLE
 - 9) THE TOOL MUST BE PACKAGED WITH A DESICCANT BAG INTO A TIGHT FITTING SEALED PLASTIC BAG

A	NEW ISSUE	18-551	VM
REV.	DESCRIPTION	ECN #	BY
DESIGN	VM	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	VM		
CHECKED	VM	TOOL PART #	REV. A
MFG. APPR.	DP	RBW6320G12851-8G	SHEET 1 OF 1
APPROVED	VP	TITLE	SCALE
DATE 8/28/2018		MGB INPUT FLANGE INSTALLATION PULLER	NTS
COPYRIGHT © 2018 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.			